

Gözlü Sonsuz Halat SF:7:1 , EN 1492-2

Art No.	Renk kodu						Uzunluk min/max (m)
		Düz Kaldırma	U Kaldırma	Boğma	Açılı Kaldırmalar		
					(0 - 45°)	(45°- 60°)	
Kaldırma Kapasitesi (kg)							
2514 05 11		1000	2000	800	1400	1000	0.5 / 20.0
2514 15 11		2000	4000	1600	2800	2000	0.5 / 20.0
2514 30 11		3000	6000	2400	4200	3000	0.5 / 20.0
2514 40 11		4000	8000	3200	5600	4000	1.0 / 20.0
2514 50 11		5000	10000	4000	7000	5000	1.0 / 20.0
2514 60 11		6000	12000	4800	8400	6000	1.0 / 20.0
2514 80 11		8000	16000	6400	11200	8000	1.0 / 20.0

*Talep üzerine farklı uzunluk, renk ve kapasitede üretim yapılabilir.

*Yukarıdaki kapasite tablosu simetrik yük kaldırmaları için geçerlidir.



- Sapan renginde çıkarılıp takılabilir kılıfı bulunur.
- Ek kılıf, sapanın yaşam ömrünü uzatır.
- Masterlink ve kanca ile çok bacaklı sapan yapımında kullanılır.
- Yüksek UV koruması mevcuttur.
- Hasar dayanımı yüksek ilave PU emdirilmiştir.